

Jet pumps EColution with integrated C-profile and built-in pneumatic control



C-PROFILE

* Nipple with 1/4" thread – different 1/4" connections possible - see chapter fitting

with integrated C-profile

suitable for mounting with quick fix vario (series 26111X) - see chapter legs

cable length: 2 m with wire end ferrules

system of protection: IP X5

One mini jet is equivalent to about 3 micro jets.



Photo	line voltage	input	output	length	mini jets	test mark	weight	Order No.
with self-drain - 50 Hz								
A	220 - 240V 50Hz	0,54 hp 0,40 kW	0,28 kW	315 mm	4 - 6	CE, ÖVE	4.4 kg	1711-WEP
A	220 - 240V 50Hz	0,82 hp 0,60 kW	0,45 kW	315 mm	6 - 8	CE, ÖVE	5.2 kg	1712-WEP
A	220 - 240V 50Hz	1,10 hp 0,80 kW	0,55 kW	315 mm	8 - 12	CE, ÖVE	5.6 kg	1713-WEP
A	220 - 240V 50Hz	1,50 hp 1,10 kW	0,75 kW	339 mm	12 - 16	CE, ÖVE	7.4 kg	1714-WEP
with self-drain - 60 Hz								
A	220 - 240V 60Hz	0,54 hp 0,40 kW	0,28 kW	315 mm	4 - 6	CE	4.3 kg	1711-WEP-60
A	220 - 240V 60Hz	0,82 hp 0,60 kW	0,45 kW	315 mm	6 - 8	CE	5.3 kg	1712-WEP-60
A	220 - 240V 60Hz	1,10 hp 0,80 kW	0,55 kW	315 mm	8 - 12	CE	5.8 kg	1713-WEP-60
A	220 - 240V 60Hz	1,50 hp 1,10 kW	0,75 kW	339 mm	12 - 16	CE	7.4 kg	1714-WEP-60
with evacuation nipple - 50 Hz *								
B	220 - 240V 50Hz	0,54 hp 0,40 kW	0,28 kW	286 mm	4 - 6	CE, ÖVE	4.2 kg	1711-WNP
B	220 - 240V 50Hz	0,82 hp 0,60 kW	0,45 kW	286 mm	6 - 8	CE, ÖVE	5 kg	1712-WNP
B	220 - 240V 50Hz	1,10 hp 0,80 kW	0,55 kW	286 mm	8 - 12	CE, ÖVE	5.4 kg	1713-WNP
B	220 - 240V 50Hz	1,50 hp 1,10 kW	0,75 kW	310 mm	12 - 16	CE, ÖVE	7.2 kg	1714-WNP
with evacuation nipple - 60 Hz *								
B	220 - 240V 60Hz	0,54 hp 0,40 kW	0,28 kW	286 mm	4 - 6	CE	4.3 kg	1711-WNP-60
B	220 - 240V 60Hz	0,82 hp 0,60 kW	0,45 kW	286 mm	6 - 8	CE	5.2 kg	1712-WNP-60
B	220 - 240V 60Hz	1,10 hp 0,80 kW	0,55 kW	286 mm	8 - 12	CE	5.6 kg	1713-WNP-60
B	220 - 240V 60Hz	1,50 hp 1,10 kW	0,75 kW	310 mm	12 - 16	CE	7.3 kg	1714-WNP-60
with cartridge drain - 50 Hz								
C	220 - 240V 50Hz	0,54 hp 0,40 kW	0,28 kW	275 mm	4 - 6	CE, ÖVE	4.2 kg	1711-WCP
C	220 - 240V 50Hz	0,82 hp 0,60 kW	0,45 kW	275 mm	6 - 8	CE, ÖVE	5 kg	1712-WCP
C	220 - 240V 50Hz	1,10 hp 0,80 kW	0,55 kW	275 mm	8 - 12	CE, ÖVE	5.4 kg	1713-WCP
C	220 - 240V 50Hz	1,50 hp 1,10 kW	0,75 kW	298 mm	12 - 16	CE, ÖVE	7.1 kg	1714-WCP
with cartridge drain - 60 Hz								
C	220 - 240V 60Hz	0,54 hp 0,40 kW	0,28 kW	275 mm	4 - 6	CE	4.3 kg	1711-WCP-60
C	220 - 240V 60Hz	0,82 hp 0,60 kW	0,45 kW	275 mm	6 - 8	CE	5.1 kg	1712-WCP-60
C	220 - 240V 60Hz	1,10 hp 0,80 kW	0,55 kW	275 mm	8 - 12	CE	5.7 kg	1713-WCP-60
C	220 - 240V 60Hz	1,50 hp 1,10 kW	0,75 kW	298 mm	12 - 16	CE	7.2 kg	1714-WCP-60

